



Report

Long Term Void Water Storage and Quality

21 SEPTEMBER

Prepared for
BMA Coal Pty Ltd
Level 23 Riparian Plaza
71 Eagle Street
Brisbane QLD 4000

42626420



Asst. Project Manager:




S. Denner
Associate Hydrogeologist

URS Australia Pty Ltd

**Level 16, 240 Queen Street
Brisbane, QLD 4000
GPO Box 302, QLD 4001
Australia**

**T: 61 7 3243 2111
F: 61 7 3243 2199**

Project Director:



C. Pigott
Senior Principal

Author:



M. Stewart
Principal Hydrogeologist



V. Edwards
Environmental Engineer

Reviewer:



M. Tsou
Associate Groundwater
Modeller

Date:
Reference:
Status:

21 September 2009
42626420/Void/3
Final Draft

© Document copyright of URS Australia Pty Limited.

This report is submitted on the basis that it remains commercial-in-confidence. The contents of this report are and remain the intellectual property of URS and are not to be provided or disclosed to third parties without the prior written consent of URS. No use of the contents, concepts, designs, drawings, specifications, plans etc. included in this report is permitted unless and until they are the subject of a written contract between URS Australia and the addressee of this report. URS Australia accepts no liability of any kind for any unauthorised use of the contents of this report and URS reserves the right to seek compensation for any such unauthorised use.

Document delivery

URS Australia provides this document in either printed format, electronic format or both. URS considers the printed version to be binding. The electronic format is provided for the client's convenience and URS requests that the client ensures the integrity of this electronic information is maintained. Storage of this electronic information should at a minimum comply with the requirements of the Commonwealth Electronic Transactions Act (ETA) 2000.

Where an electronic only version is provided to the client, a signed hard copy of this document is held on file by URS and a copy will be provided if requested.

Table of Contents

Executive Summary	iv
1 Introduction	1
1.1 Available data	1
1.2 Background	1
2 Model scenarios	3
2.1 Model Approach	3
3 Model Conceptualisation	5
3.1 Data review	5
3.1.1 Head and concentration data	5
3.1.2 Boundary conditions	5
3.1.3 Aquifer properties	7
4 Model Input Data	8
4.1 Rainfall	8
4.2 Evaporation	9
4.3 Aquifer parameters	10
4.4 Runoff	10
4.4.1 Verification	10
4.4.2 Input into model	11
4.5 Hydrochemistry	11
5 Model Set-up	13
5.1 Grid Extent	13
5.2 Model layers	13
5.3 Boundaries	13
5.4 Parameterisation	13
5.4.1 Hydraulic conductivity (K)	13
5.4.2 Recharge and Evaporation	17
5.5 Assumptions	17
6 Modelling Results	18
6.1 Sensitivity analysis	18
6.2 Simulations	20

6.3	Salt balance	21
6.4	Spill risks	22
6.5	Groundwater / Void Water Interaction	23
6.6	Flood Risk.....	23
6.7	Stratification	23
7	Conclusions.....	25
8	Limitations.....	26

Tables

Table 3-1	Model Layer assigned values	7
Table 4-1	Significant rainfall events on record.....	9
Table 4-2	Aquifer parameters	10
Table 4-3	EC and TDS data.....	11
Table 4-4	Representative salinity data.....	12
Table 5-1	Hydraulic conductivity data	14

Figures

Figure 3-1	Groundwater contours	6
Figure 4-1	Average monthly rainfall (100 years).....	8
Figure 4-2	Evaporation data.....	9
Figure 5-1	Grid extent.....	15
Figure 5-2	Schematic W-E cross-section showing the model layers.....	16
Figure 6-1	Drawdown simulation at end of mining (base case final void).....	19

Drawings

Drawing 1-1	Typical drawdown cone	2
-------------	-----------------------------	---

Appendices

Appendix A	Final void configurations
Appendix B	Final void water level figures
Appendix C	Salt balance and Void Volumes figures
Appendix D	Drawdown cone predictions

Abbreviations

Abbreviation	Description
m AHD	metres above Australian Height Datum
BMA	BHP Billiton Mitsubishi Alliance
C	Runoff coefficient
CLIMARC	Computerising the Australian Climate Archives
DERM	Department of Environment and Resource Management
EC	Electrical conductivity
EIS	Environmental impact statement
K	Hydraulic conductivity (m/day)
km	kilometres
m/day	metres per day
MODHMS	Integrated modelling software package
PEST	Parameter estimation
PWB	PW Baker & Associates Pty Ltd
Q	Discharge rate
TDS	Total dissolved solids
URS	URS Australia Pty Ltd

Executive Summary

URS were appointed to conduct an assessment of the hydrological and salinity performance on a range of final void scenarios for the proposed Caval Ridge Mine. A scope of work was envisaged by Peter Baker & Associates, which included integrated modelling to address the long-term water and salt balances for three final void configurations. The modelling aimed at assessing decant and flooding risks, connections to groundwater resources, and water quality parameters in the long term.

The three final void configurations includes a base case, the void at the end of mining ~ 156 m deep; a 25% regrade (25p) resulting in a shallower final void (~ 123 m) and reduced low and high walls; and a 10% regrade (10p) final void with a shallow final void (~ 55 m) and gentle slopes.

An integrated (surface water and groundwater) modelling approach was adopted to simulate groundwater ingress or outflow, surface water contributions, and climate influences. This allowed for the prediction of void equilibrium water level and estimates of salt accumulation for each of the three void configurations. In order to provide representative scenarios the input into the modelling included two different surface water catchment areas and three different long term rainfall predictions. A sensitivity analysis was included during modelling with regards to aquifer hydraulic parameters and a verification process, using a rainfall-runoff model, to determine representative surface water runoff volumes.

A nine layer (based on site geology) model comprised a 100 m x 100 m grid across a 74.4 km² area was constructed. The model extent was deemed sufficiently large to assign constant head boundaries (based on extrapolated groundwater level data) in predicting long term groundwater trends. The 100 year mean annual rainfall and evaporation data and representative aquifer hydraulic parameters were used as input into the model set up.

A steady state model, using MODHMS software, was constructed based on the available data and represented envisaged groundwater flow conditions after 30 years of mine dewatering. The steady state model outcome was used as initial conditions for the transient model, which undertook the predictive scenarios.

The transient model was constructed, based on representative model parameters, and was verified through sensitivity analyses and review of model water budgets. It was used to predict resulting water levels and salt concentration in various final void configurations due to groundwater rebound and changes in runoff and climate (rainfall and evaporation) conditions. The final void equilibrium water levels were estimated for the three void configurations and were compared to the pre-mining groundwater levels. A salt balance for each of the final void configurations was calculated to predict long-term water quality trends.

The shallow final void, which included higher than average rainfall and a larger catchment area, is recognised to have the lowest long term impacts on final void water quality. Final void water is, however, recognised to deteriorate with time for all scenarios considered.

Due to low rainfall, high evaporation, and limited groundwater ingress the final void (irrelevant of configuration) does not contain significant volumes of water after void water equilibrium is reached. The remaining large void storage space is sufficient such that the risk of decant is negligible.

Consideration of flood protection is being considered by URS in their flood study for the Caval Ridge EIS supplementary submission.

Introduction

BHP Billiton Mitsubishi Alliance (BMA) are investigating and considering stable, sustainable outcomes and void footprint minimisation strategies for the envisaged final voids at Caval Ridge Mine. To demonstrate this BMA have appointed URS to conduct an assessment of the hydrological and salinity performance on a range of void scenarios.

PW Baker & Associates Pty Ltd (PWB) will, on behalf of BMA, be compiling the necessary final void report. PWB have developed a scope of work which includes integrated (surface water and groundwater) modelling to address the long-term water and salt balances in the envisaged void configurations. The modelling aims at assessing decant and flooding risks, connections to groundwater resources, and water quality parameters in the long term.

URS were asked to prepare a brief report of the modelling to indicate methodology, data sources, and model limitations.

1.1 Available data

To assist in selecting and setting up the necessary numerical integrated model, the following information was considered:

- The project site, comprising the Horse Pit, is approximately 10 km x 5 km;
- The coal dips at $\sim 6^\circ$ to the east;
- The final pit depth will be ~ 200 m;
- The geology within the pit comprises Quaternary alluvial, Tertiary sediments, and Permian coal measures;
- Only the Horse Pit final void is to be modelled;
- The surface water diversions, around the Horse Pit, will remain after closure;
- No major faults or intrusions are located within the Horse Pit mining void;
- Bore logs and hydrogeological data for 16 monitoring bores across the site;
- 5 sets of groundwater monitoring, water levels and quality, data;
- Shape files for the topography, alluvium, tertiary, and coal seams; and
- Surface water data from the EIS.


1.2 Background

Current available data, groundwater levels and ambient hydrochemistry, are based on pre-mining conditions. Therefore it is important to relate the available data to the aquifer conditions when dewatering ceases such that suitable starting conditions can be established for the purpose of long-term model predictions.

Pumping of water (groundwater ingress, runoff and direct rainfall) will result in the dewatering of the hanging wall sediments, ahead of mining and along strike. Drawing 1-1 indicates a typical dewatering cone which develops ahead of surface mining.

1 Introduction

Drawing 1-1 Typical drawdown cone



The extent of the drawdown cones, as calculated in the EIS groundwater section, around the voids was less than 1 km (839 m in the interburden).

The size distribution of coal overburden spoil material is highly variable based on geology, dumping method, and placement (dragline or truck). This can result in variable permeability across the backfill area and over time. Increased recharge and alteration, due to increased total dissolved solids, to the groundwater quality is envisaged to occur within the backfill. Based on limited data it is assumed that the hydraulic conductivity, runoff and TDS contribution from the spoil pile remains constant throughout the modelled scenarios.

The lower hydraulic conductivity (K) of the foot wall sediments and the base of the spoil having higher K reduces the impacts of dewatering within the foot wall sediments.

These impacts were considered when setting up the model and conducting scenario predictions, such as groundwater rebound and salt balances.

Model scenarios

Three final void configurations have been provided for inclusion in the modelling. These include:

- Base case, the 30 year mine configuration with standing highwall and steep ramps and lowwalls;
- 25p regrade case, the pits and ramps have been reshaped to approximately 25%; and
- 10p regrade case, the pit and ramps have been reshaped to 10%.

Appendix A includes the three mine void configurations.

The modelling simulates groundwater ingress or outflow, surface water contributions, climate influences, and resultant salt balances for each of the three void configurations.

Each of the three configurations will result in markedly different storage volumes based on predicted equilibrium void water levels. Modelling is also required to allow for two different surface water ingress scenarios when considering the void water levels. These two surface water scenarios include:

- Limited catchment area, surface water inflow is limited to direct rainfall and runoff into the void without any modifications (min); and
- Maximum catchment area, as above but with the runoff from the backfill spoils piles being captured in a drainage system and redirected into the void (max).

In order to provide representative long term simulations three different climate scenarios were considered. The modelling allowed for the consideration of the following rainfall scenarios:

- Dry case, the mean annual precipitation reduced by 10%;
- Median case, the mean annual precipitation based on 100 years of data; and
- Wet case, the mean annual precipitation increased by 10%.

A sensitivity analysis was included with regards to aquifer hydraulic parameters. The aquifer hydraulic parameters utilised for the model were estimated based on the EIS groundwater study, the drilling and testing of 16 monitoring bores. The parameters were varied within expected ranges to determine sensitivity. The parameters which were varied were:

- Hydraulic conductivity values, low, medium, and high; and
- Runoff coefficients for the backfill spoil areas, low, medium, and high.

2.1 Model Approach

URS utilised the MODHMS groundwater modelling package to construct the required groundwater model. MODHMS was selected as it allowed for:

- The modelling of variable saturation conditions, allowing for unsaturated and saturated conditions thus avoiding dry-cell problems;
- Coupled flow and mass transport simulations;
- The inclusion of discrete features, such as the backfill area; and
- Integrated groundwater and surface water modelling.

A steady state model was constructed based on the available data and represented envisaged groundwater flow conditions at the end of the 30 years life of mine. The steady state model outcome (drawdown extent) was used as initial conditions for the transient model, which undertook predictive scenarios. The modelling approach comprised the following:

2 Model scenarios

- Simulations of dewatering cones and extent at the end of mining (after 30 years and final void depth to ~ 160 m below surface);
- Groundwater ingress volumes with time and void water level rebound to an equilibrium level (some 40 to 50 years after mining); and
- Salt balance assessment through the integrated modelling of surface water and groundwater input and climate effects.

A rainfall-runoff model was compiled, which utilised the daily rainfall and evaporation data for the 100 year dataset, to estimate the volume of water within the final void after 100 years. This allowed for an accurate estimate of the runoff volume for inclusion in the rational formula. Using the rational formula an estimation of the runoff coefficient was calculated for inclusion in the integrated model. The estimated runoff was then used as an input into the model, which allowed for the determination of equilibrium water levels in the final void, allowing for different catchment sizes and rainfall scenarios.

Model Conceptualisation

The approach presented includes the steps and plans needed to construct a suitable groundwater numerical model.

3.1 Data review

Geological and hydrogeological data compiled from the groundwater studies for the study area have been compiled and reviewed. The majority of the data is compiled in Chapter 7 of the Caval Ridge Environmental Site Assessment report (URS, 2009), which included bore logs, aquifer tests, and hydrochemistry. Available groundwater data from the Department of Environment and Resource Management (DERM) bore database have been obtained and reviewed.

Three main data requirements have been identified as crucial to the construction of the envisaged numerical groundwater model, these data requirements include:

- Dependent variables (head and concentration data);
- Boundary conditions; and
- Aquifer properties.

3.1.1 Head and concentration data


Groundwater level and hydrochemical data from bores within the weathered and fractured rock aquifers were compiled, verified, and analysed. The groundwater level data has been contoured in order to evaluate the pre-mining groundwater flow patterns, gradients, and direction(s) on the site. The groundwater level contours are presented in Figure 3-1 and serve as regional flow trends for generating model initial conditions.

3.1.2 Boundary conditions


Model boundaries are based on available information and site data limitations. The boundaries include:

- **Top inflow boundary** comprising recharge and evaporation. Available precipitation and evaporation data was reviewed / verified;
- **Horizontal inflow boundary** based on groundwater level data, which is used to determine the sites' east, west, north, and south boundary conditions. Geological log data and groundwater level information was used to set up representative constant head boundaries, sufficiently far from the mine; and
- **Bottom inflow boundary** considered below the site. Model bottom elevations were determined from floor and roof elevation data supplied by the client. The no-flow boundary was assumed sufficiently far below the Layer 9 floor elevation based on available geological data.

NOTE: As the modelling was limited to only the Horse Pit final void a constant head boundary has been included along the southern boundary of the model grid. This approach removes the cumulative impacts of the Heyford Pit, which is to be constructed along strike of the Horse Pit.



This drawing is subject to COP/PR/GRHT. It remains the property of URS Australia Pty. Ltd.

Client  BHP Billiton Mitsubishi Alliance	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title PRE-MINING GROUNDWATER LEVELS	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1502.mxd	Date: 22-09-2009	Figure: 3-1

3 Model Conceptualisation

3.1.3 Aquifer properties

Limited site specific aquifer hydraulic parameters are available for the various geological and hydrogeological units mapped on site. In order to assist with the construction of groundwater model layers the following aquifer properties are evaluated:

- Hydraulic conductivity (K), derived from slug tests conducted in order to obtain aquifer hydraulic parameters; and
- Storage properties of aquifers (unconfined and confined), obtained from literature values.

The aquifer parameters utilised for the initial model set-up are summarised in Table 4-1.

Table 3-1 Model Layer assigned values

Unit	K (m/day)	Specific yield	Specific storage (/m)
Coal seams	0.17	0.03	0.00001
Inter/Overburden	0.03	0.03	0.00001
Backfill	0.22	0.10	-

Model Input Data

4.1 Rainfall

Recorded site specific data, from the Moranbah weather station, is available for the period 1972 to 2007. For an extended period (100 years) a statistical analysis of climate data from surrounding weather stations was compiled based on the DERM Data Drill system.


The rainfall and evaporation data for a selected point, 22°15'S 148°12'E, within the mine site was interpolated from 25 daily observations using anomaly interpolation method for CLIMARC¹ data.

The Data Drill rainfall data for the period 13/11/1908 to 13/11/2008 provided the following:

- Average daily rainfall (over 100 years) 1.55 mm; and
- Average daily rainfall for each year.

Figure 4-1 shows the average monthly rainfall data for the 100 years of data.

Figure 4-1 Average monthly rainfall (100 years)



The daily rainfall data for 100 years included the most significant rainfall events recorded within the area. Table 4-1 present the most significant rainfall events, which indicates the nature of the intense storms and cyclonic rain within the study area.

¹ CLIMARC – Computerising the Australian Climate Archives

4 Model Input Data

Table 4-1 Significant rainfall events on record

Date	Volume (mm)	Duration (days)
Highest recorded rainfall		
08/01/1991	385.1	15
12/02/1954	326.7	13
22/03/1910	318.8	18
07/04/1958	309.8	11
06/01/1917	296.5	12
Longest rainfall duration		
17/02/1947	201.6	19
24/01/1946	106.1	19
22/03/1910	318.8	18
06/04/1963	179.3	17
08/05/2000	158.7	17


The mean annual rainfall, for the 100 years, was calculated and used as input into the model. In order to assess the impacts of climate fluctuations a 10% variation (dry and wet) to the mean annual rainfall was simulated in the model to determine variations in the equilibrium water levels of the three final void configurations.

4.2 Evaporation

The evaporation data was determined, based on the Data Drill system, for the 100 years of most recent data, 31/12/1907 to 31/12/2007. The average daily evaporation, over 100 years, was calculated to be 5.77 mm.

Figure 4-2 shows the average monthly evaporation data for the 100 year data.

Figure 4-2 Evaporation data



4 Model Input Data

The average annual rainfall and evaporation data indicates a negative water balance for the study area with evaporation exceeding rainfall for all months of the year.

4.3 Aquifer parameters

An evaluation of the data presented in the Groundwater Section of the EIS allowed for the selection of representative aquifer parameters. The parameters are presented in Table 4-2.

Table 4-2 Aquifer parameters

Lithology	Parameter	Minimum	Maximum	Selected
Coal seams	K (m/day)	0.017	1.7	0.17
	Specific yield	1%	5%	5%
	Storage Coefficient	0.0001	0.001	0.001
Inter/Overburden	K (m/day)	0.003	0.3	0.03
	Specific yield	1%	5%	3%
	Storage Coefficient	0.00001	0.001	0.001
Backfill	K (m/day)	0.022	2.2	0.22
	Specific yield	5%	15%	15%

4.4 Runoff

Runoff is subjected to rainfall intensity and antecedent moisture conditions of the soil. A low total runoff was envisaged for the study area due to mostly drier soil conditions (bare land and high evaporation rate) and areas of higher infiltration (backfill areas). In addition, the intensity of most rainfall events may not be high enough to produce significant runoff.

The rainfall data used in the model was not generated from intensity-duration-frequency curves; instead it was a calculated 100-year mean annual rainfall value (565 mm/year). The use of a mean annual rainfall value meant runoff was generated daily and cumulated for 100 years. It was envisaged that this runoff volume (generated from mean rainfall) was in the same order or close to volume that would be generated from significant rainfall events (rainfall events with sufficient intensity and duration to allow runoff).

The integrated model, comprising nine layers, was simplified to reduce model running time and allow for a conservative estimate of void water volumes over time based on a mean annual rainfall of 565 mm/year. The simplified model approach allowed for net recharge to be added directly to the groundwater system taking into consideration high evaporation, high infiltration in the spoil area and most rainfall events may not have sufficient intensity to generate runoff.

The water budget generated in the model was assessed to determine if the model converged, i.e. parameters were altered (within appropriate boundaries) to reduce the discrepancy between input volume to and output volumes from the system.

4.4.1 Verification

In order to assess the validity of estimated surface water runoff component of the water budget the integrated model was utilised to conduct a rainfall-runoff simulation. The mean annual rainfall value of

4 Model Input Data

1.54 mm/day was determined from the 100 year dataset. The 100 year daily and monthly rainfall and evaporation data sets were entered into the model to verify the model runs with estimated runoff from the rational formula.

Through the verification it was concluded that a runoff coefficient of 10% could be utilised to estimate runoff into the final void, as verified based on the 100 year daily rainfall-runoff modelling. This is recognised to be more representative of the water volume in the void after 100 years.

4.4.2 Input into model

The runoff volume was then simulated in the model by injecting water along the boundary of the catchment (both max and min), which allowed for the simulation of overland flow. The parameters considered for overland flow include:

- Daily rainfall data for 100 year dataset;
- Daily evaporation data for 100 year dataset;
- A Manning coefficient of 0.15 or less (bare ground) after a sensitivity analysis;
- Rill height of 1 mm (highly sensitive parameter which resulted in large range of volumes reporting to the void); and
- Obstruction height was negligible (not a typical feature in this case).

This allowed for a more accurate volume of water, reporting to the final void over time, to be estimated. The runoff volumes entering the void were included in the calculation of the salt balance, as the runoff across the spoil was assumed to contain a TDS of 450 mg/L (Section 4.5).

4.5 Hydrochemistry

The field measurements recorded during the EIS groundwater study and during subsequent monitoring rounds were used to determine representative groundwater water quality inputs, in terms of salinity, for each of the lithological units modelled on site.

The recorded electrical conductivity data and calculated Total Dissolved Solids² (TDS) data is presented in Table 4-3.

Table 4-3 EC and TDS data

Monitoring	Unit	EC readings ($\mu\text{S}/\text{cm}$)			Average EC	Calculated TDS (mg/L)
		June 2008	September 2008	February 2009		
Bore						
Pz03-D	Coal seam D04	19 970	21 450	16 570	19 330	12 371
Pz04	Coal seam Q	1 529	1 107	1 111	1 249	800
Pz06-D	Coal seam P02	1 691	1 981	1 813	1 828	1 170
Pz07-S	Alluvium	-	351	443	397	250
Pz07-D	Coal seam Q01	-	3 890	3 960	3 925	2 510
Pz08-S	Alluvium	-	1 861	2 129	1 995	1 280
Pz08-D	Interburden	-	12 510	11 380	11 950	7 640

² TDS (mg/L) = EC ($\mu\text{S}/\text{cm}$ *A), where A is between 5.5 and 9 depending on the chemical composition of the sample. A = 0.64 was utilised for the calculated TDS.

4 Model Input Data

Pz09	Coal seam P08	-	12 510	9 790	11 150	7 140
Pz10	Coal seam H08	-	9 090	-	9 090	5 820
Pz11-D	Coal seam P08	-	8 650	7 220	7 940	5 080

Previous studies within the area plus an evaluation of the data presented in Table 4-2 allowed for the selection of representative TDS (salinity) inputs into the salt balance for the modelling. These data are compiled in Table 4-4.

Table 4-4 Representative salinity data

Water source	Electrical conductivity ($\mu\text{S/cm}$)	TDS (mg/L)
Alluvium groundwater	390 to 2 000	250 to 1 280
Inter / overburden groundwater	12 000	7 500
Coal groundwater	16 000	10 000
Rain	16	10
Runoff from disturbed areas	700	450
Runoff from undisturbed areas	300	170

In order to calculate a first approximation of the salt balance based on relative contributions the following assumptions have been made:

- An average TDS value of 9 000 mg/L has been assigned for the groundwater ingress. This is based on a 60% contribution from coal (10 000 mg/L TDS) and 40% from the inter/overburden units (7 500 mg/L); and
- All runoff modelled is derived from disturbed areas, thus a TDS value of 450 mg/L was utilised in the model.

Model Set-up

5.1 Grid Extent

Based on the drawdown radius of influence envisaged in the EIS groundwater chapter (Section 2) the model grid was constructed to extend over an area of 74.4 km² to envelope the final void. The grid extends 6.2 km from west to east and 12 km from north to south. The grid cell size is 100 m x 100 m.

The distances to the boundaries are sufficiently far away from the void that constant head boundaries could be assigned based on the pre-mining groundwater level data (Figure 3-1).

Figure 5-1 shows the final grid extent and configuration across the study area.

5.2 Model layers

Nine layers, representing the different lithological units across the site, were included in the model. The layers were constructed based on the roof and floor contours of the coal seams and the topography supplied by the client. These units were extrapolated to the east to the boundary of the model.

Figure 5-2 presents a west-east cross-section through the centre of the model, illustrating the model layers. The model layers are as follows:

Layer 1:	Unconfined weathered overburden aquifer
Layer 2:	Coal
Layer 3:	Interburden
Layer 4:	Coal
Layer 5:	Interburden
Layer 6:	Coal
Layer 7:	Interburden
Layer 8:	Coal
Layer 9:	Interburden

5.3 Boundaries

Section 3.1.2 discusses the boundaries included in the model.

5.4 Parameterisation

5.4.1 Hydraulic conductivity (K)


In order to obtain an initial assessment of the final void water the aquifer hydraulic parameters, hydraulic conductivity and storativity, were assumed to be homogeneous within each model layer.

Representative K data was based on site specific data compiled during the variable (slug) head tests conducted across the study area. The K data, as determined during the EIS compilation, is presented in Table 5-1.

5 Model Set-up

Table 5-1 Hydraulic conductivity data

Monitoring well	Unit	Hydraulic Conductivity (K) (m/day)	
		Bouwer & Rice Method	Hvorslev Method
Pz01	Coal seam D04	0.1	0.13
Pz02	Basalt	0.005	0.006
Pz03-S	Basalt	0.08	0.1
Pz03-D	Coal seam D04	0.5	0.6
Pz04	Coal seam Q	0.3	0.3
Pz05	Coal seam D04	0.02	0.03
Pz06-S	Basalt	0.1	0.2
Pz06-D	Coal seam P02	0.06	0.08
Pz07-S	Alluvium	0.3	0.4
Pz07-D	Coal seam Q01	0.3	0.3
Pz08-S	Alluvium	0.09	0.1
Pz08-D	Sandstone interburden	0.03	0.03
Pz09	Coal seam P08	0.1	0.2
Pz10	Coal seam H08	0.03	0.04
Pz11-S	Alluvium	Dry	Dry
Pz11-D	Coal seam P08	0.03	0.04





This drawing is subject to COPVPI/GHT. It remains the property of URS Australia Pty Ltd.

Installed Monitoring Wells
 Project Site
 Mining Lease
 Extent of Modelled Area


Kilometers
 0 0.5 1 2 3 4

Scale 1:100 000 (A4)
 Datum: AGD84, AMG Zone55

Source:		Client		Project		Title	
 BHP Billiton Mitsubishi Alliance				CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		GRID EXTENT AND SITE LAYOUT	
				Drawn: MG	Approved: MST		
Job No: 4262 6420/6158				File No.: 42626158-g-1503.mxd		A4	





Horizontal Axis -
1 Block width = 100m



Vertical Axis: Horizontal Axis
5:1

LEGEND

Top Elevation of Layer (mAHD)



This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty Ltd.

Source:

Client

Project
CAVAL RIDGE PROJECT
ENVIRONMENTAL IMPACT STATEMENT
SUPPLEMENT
LONG TERM VOID WATER STORAGE AND QUALITY

Title
**SCHEMATIC CROSS SECTION
W-E - ELEVATIONS OF
MODEL LAYERS IN GRID**

Drawn: MG	Approved: MST	Date: 22-09-2009
Job No: 4262 6420/6158	File No.: 42626158-g-1504.mxd	

Figure: 5-2	Rev. A
	A4

5 Model Set-up

5.4.2 Recharge and Evaporation

Rainfall recharge to the undisturbed Tertiary sediments and Permian coal seams is recognised to be low, < 5% of mean annual precipitation within the study area. Recharge zones were classified based on the rock types across the site, with the highest recharge being allocated to the backfill spoil pile area.

The recharge was refined through a review of the model water budget. Evaporation was estimated from the same process.

5.5 Assumptions

The following assumptions were made when constructing and running the integrated model:

- The physical and chemical properties of the spoil pile remain constant through out the modelled period;
- The Heyford Pit was not included in the simulations and thus cumulative impacts of drawdown cones from the Horse and Heyford voids was excluded from the modelling;
- Groundwater levels used to set constant head boundaries were derived from the extrapolation of groundwater data recorded within the middle of the model grid;
- Model layer elevations were interpolated based on available roof and floor elevation data. Uniform layer thickness was extended to the model boundaries for the areas where no data was available;
- The numerical errors resulting from the dipping angles of the model layers were assumed to be negligible. The possible discrepancy can be reduced by including the effect into hydraulic conductivity;
- Groundwater levels are relatively deep below surface. Evaporation and transpiration impacts on groundwater are therefore recognised to be of limited significance. Evaporation and transpiration are, however, considered and combined into recharge as net recharge for the areas outside the mining area. Evaporation from land surface is considered only in the mining area, which accounts the major contribution from the void;
- Hydraulic conductivity and storativity are assumed to be homogeneous within each model layer;
- Head boundaries were extrapolated based on water level data in 2009 and were assumed to keep constant during the simulation period;
- Groundwater levels were assumed to be uniformly distributed across all layers, i.e. the same groundwater level was assigned to each layer;
- Net recharge was considered to be 2 to 3 percent of mean annual rainfall outside the mining area. No net recharge was applied within the mining area (maximum or minimum catchment area); and
- The integrated model has an overland flow domain, which simulates runoff, interactions with groundwater, and direct evaporation from surface. Since 100 year mean annual precipitation was adopted in the simulation, runoff can not be sufficiently generated, so rainfall-runoff simulation was not conducted explicitly and was approximated by the rational formula.

Modelling Results

Once the groundwater model was set-up based on the pre-mining groundwater levels the model was used to simulate the predicted groundwater level drawdown around the final void after 30 years of mining, to simulate the gradients expected based on the base case final void configuration. The simulated drawdown around the mine is presented in Figure 6-1.

Using this model the following outputs were compiled:

- Final void water level simulations for each of the three void configurations (base, 25p regrade, and 10p regrade), using two catchment configurations (minimum and maximum), three climate conditions (mean annual rainfall, + 10%, and – 10%), as discussed in Section 3;
- A comparison of predicted equilibrium void water levels to pre-mining groundwater levels;
- A salt balance for each of the final void configurations based on predicted groundwater ingress, variable climate data, and different catchment sizes, for 100 years; and
- An estimate of void space within each of the three void configurations after equilibrium is reached, which allowed for an evaluation of probability of spill risk.

In addition, URS were asked for input regarding flood risk and stratification within the final void.

6.1 Sensitivity analysis









Table 6-1 shows the Modelling Runs conducted to perform Analysis and Sensitivity Results for the envisaged scenarios presented above.


The sensitivity analysis allowed for the selection of the optimum parameters to conduct the model simulations.

Legend


-  Initial Head Base
-  Project Site
-  Mining Lease

**Initial Head Basecase
(mAHD)**



-  160 - 170
-  171 - 180
-  181 - 190
-  191 - 200
-  201 - 205
-  206 - 210
-  211 - 215
-  216 - 220



Scale 1:40 000 (A4)
Datum: AGD84, AMG Zone55



Source:

Client  BHP Billiton Mitsubishi Alliance	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title DRAWDOWN SIMULATION (BASE CASE) AT END OF MINING	
		Drawn: MG	Approved: MST	Date: 22-09-2009
Job No: 4262 6420/6158		File No.: 42626158-g-1505.mxd		Rev. A A4

This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty, Ltd.

6 Modelling Results

Table 6-1 Modelling Scenarios

	Contour Grading	Contributing Area	Rainfall	K Value	Runoff Coefficient
Analysis	Base	maximum	median	Base Scenario	0.1
			+10%	Base Scenario	0.1
			-10%	Base Scenario	0.1
		minimum	median	Base Scenario	0.1
			+10%	Base Scenario	0.1
			-10%	Base Scenario	0.1
	10p regrade	maximum	median	Base Scenario	0.1
			+10%	Base Scenario	0.1
			-10%	Base Scenario	0.1
		minimum	median	Base Scenario	0.1
			+10%	Base Scenario	0.1
			-10%	Base Scenario	0.1
	25p regrade	maximum	median	Base Scenario	0.1
			+10%	Base Scenario	0.1
			-10%	Base Scenario	0.1
minimum		median	Base Scenario	0.1	
		+10%	Base Scenario	0.1	
		-10%	Base Scenario	0.1	
Sensitivity	Base	minimum	median	Base Scenario	0.1
				Base Scenario	0.1
			+10%	0.1	
			-10%	0.1	

Note: Base Scenario K values= Coal 0.17, Inter/Overburden 0.03, Backfill 0.22

6.2 Simulations

Final void volumes were calculated using modelling results, these are shown in **Appendix B**. Selected observation locations were chosen at grid cells listed below and displayed in Figures B4-B6. Water level rebound graphs for these observations are also shown in **Appendix B**.

Observation locations	Row	Column
Obs1	48	76
Obs2	91	78

A summary of the equilibrium final void water level elevations are presented in Table 6-2.

6 Modelling Results

Table 6-2 Final void equilibrium water levels (based on mean annual rainfall)

Final void configuration	Pre-mining groundwater level at selected point	Bottom elevation of pit (m AHD)	Void equilibrium water level (m AHD)	Lowest surface elevation (m AHD)	Void equilibrium depth (m below surface ³)	Time to reach equilibrium (years)
Base case min	208.07	68.92	91.703	220	128	45
Base case max			91.739		128	50
25p regrade min	208.07	127.12	140.68		79	50
25p regrade max			144.51		75	40
10p regrade min	208.07	184.66	194.39		26	45
10p regrade max			195.00		25	30

The variation in the estimated equilibrium void water levels was calculated based on the variation in mean annual rainfall data. Table 6-3 presents the variations.

Table 6-3 Equilibrium void water levels

Final void configuration	Pre-mining groundwater level at selected point	Bottom elevation of pit (m AHD)	Void equilibrium water level (m AHD)		
			Average	+10%	-10%
Base case min	208.07	68.92	91.703	91.707	80.18
Base case max			91.739	100.36	91.732
25p regrade min	208.07	127.12	140.68	142.96	130.38
25p regrade max			144.51	147.02	144.51
10p regrade min	208.07	184.66	194.39	194.98	190.06
10p regrade max			195.00	195.00	194.736

6.3 Salt balance

Predictions of salt accumulation in the final void, for the three void configurations, was estimated based on salt contributions from groundwater ingress and runoff. Salt balance estimates were calculated for mean annual rainfall, mean +10%, and mean – 10% for each scenario.

For the base case final void scenario void water is recognised to deteriorate with time due to increased salinity. An increase in rainfall (mean +10%) and the larger catchment area results in a reduced deterioration with time. Void water, in this instance, results in an increase from ~ 5 000 mg/L TDS to ~ 12 000 mg/L TDS over 100 years.

For the most likely base case scenario; minimum catchment and average rainfall, the TDS will increase from ~ 9 800 mg/L TDS to ~ 19 800 mg/L TDS over 100 years.

³ Metres below lowest void surface elevation

6 Modelling Results

The salt accumulation for the regrade scenarios indicates similar increases with time. However, the initial increases in TDS are lower as groundwater rebound is required before it can enter the void.

The resultant charts are presented in **Appendix C**. Included in Appendix C are the estimates of net volumes in the void over time. These graphs indicate the higher the total volumes the more reduced the impact. Consideration could, therefore, be given to possibly increasing the catchment area around the final void to allow for additional runoff.

6.4 Spill risks

The probability of decant from the final void was considered for each of the three final void configurations. Based on the equilibrium water level results of the large catchment scenarios (runoff from the backfill spoil piles collected and directed into the voids) an estimate of the void space in each of the final void configurations was calculated.

The void space was calculated based on the final void figures provided by the client, which indicates the lowest elevation at the final void is 220 m AHD. Thus the void area between the equilibrium void water level and the spill elevation (220 m AHD) was calculated. Table 6-4 indicates the remaining void volumes to spill level.

Table 6-4 Void space data

Final void	Total void volume (Mm ³)	Volume of water in void at equilibrium with mean annual rainfall (Mm ³)		Percentage of total void space (%)		Void space remaining (Mm ³)	
		min	max	min	max	min	max
Base	288	2.4	5.4	0.8	1.9	285.6	282.6
25p	248	1.6	3.25	2.2	4.4	246.4	244.75
10p	73.5	1.06	1.9	0.4	0.8	72.44	71.6

The modelling indicates, based on low aquifer properties, low rainfall recharge, and high evaporation, that only a small percentage (< 6 %) of the final void will be filled with water. This results in large volumes of void space, for all three configurations, after equilibrium is reached.

An evaluation of historic climate data was conducted to determine the most significant rainfall events on record for the study area. These include:

- Largest rainfall event: 193.2 mm on 28/12/1916;
- Largest rainfall duration: 201.6 mm over 19 days recorded on 17/02/1947; and
- Largest rainfall volume: 385.1 mm over 15 days recorded on 08/01/1991.

Assuming all this water fell directly into void, i.e. 100% recharge / runoff, over the largest catchment (2 350 ha), the volumes of water reporting to the void would be:

- Largest rainfall event: 4.5 Mm³;
- Largest rainfall duration: 4.7 Mm³; and
- Largest rainfall volume: 9 Mm³.

Based on the volumes remaining in the voids (Table 6-4) none of these extreme rainfall events would have been sufficient to cause any risk of decant from the final void.

6 Modelling Results

6.5 Groundwater / Void Water Interaction

On completion of mining it is envisaged that all pumping from the final void will cease and that groundwater levels will begin to rebound. The groundwater level contours predicted for the end of mining are presented in Figure 6-1. These drawdown contours are generated such that groundwater is below the mining void to ensure a dry working area.

Groundwater rebound with time has been predicted using the numerical model. Groundwater levels will increase over time. This will result in groundwater ingress into the final void. Based on the negative water balance derived from the climate data for the area, water will be lost from the pit through evaporation such that the final void acts as a groundwater sink.

Modelling predicts final void equilibrium water levels, which are below the pre-mining groundwater levels. Thus groundwater levels will not rebound to pre-mining elevations and groundwater flow patterns will not revert back to pre-mining conditions. The mining void will, therefore, continue to impact on the local groundwater causing a localised drawdown cone around the final void.

Appendix D contains the drawdown cones predicted around each of the three final void configurations once final void equilibrium water levels (assuming mean rainfall and minimum catchment) are reached.

Data regarding neighbouring bores, presented in the Groundwater Chapter in the EIS submission, indicates that no existing bores are located within the model study area. Thus no existing users are identified within the envisaged drawdown cones resulting after equilibrium is reached in the void. It is therefore, recommended that in order to verify model predictions and to provide site specific groundwater level data away from the final void (to provide data for the constant head boundaries) additional monitoring bores be constructed outside the mine disturbed areas. Stephen Denner (URS) will be compiling an EIS supplementary response, which will include recommendations regarding suitable groundwater monitoring.

6.6 Flood Risk

The risk of flooding into the void was requested. It is considered that major flooding in the area could result in the flooding into the void. The creek diversion details were considered in terms of bank height. The required rainfall to overtop the bank was determined in terms of volume and probability (Section 7.3).

Discussions were held with Michel Raymond, Principal Water Engineer at URS, who confirmed that his department are remodelling the Caval Ridge hydrology to assess flooding. The flood scenario to be modelled will include a 1: 3000 flood event, based on 1% of the life of the mine (30 years). Based on these scenario recommendations regarding berms and flood protection measures along the north and east of the Horse Pit will be made.

Comments regarding backfill spoil pile runoff management and ramp modifications (to prevent flooding) will be included in the URS Flood Risk study.

6.7 Stratification

Water in the voids may become stratified, especially voids in arid regions as the voids may contain dense saline water after extended dry periods. Fresh water from occasional storm events will remain

6 Modelling Results

above this saline layer, based on density differences. Also a dense stable layer may form at the base of the void where water containing high concentrations of dissolved salts has flowed into the void.

The chemical and biological processes within the void water, which can influence the mobility and fate of solutes, are closely linked to stratification and destratification. Changes in speciation and solubility across oxic, suboxic, and anoxic boundaries control the solubilities of redox sensitive metals. Metals, such as chromium, lead, and selenium, are less soluble in the reduced state than in the oxidised state.

As only limited hydrology and geochemistry data is available for final voids in central Queensland, as most voids are still active components of both mining operations and mine water management systems, it will require extensive data collection through the life of the mine. These data can be modelled to assess geochemical reactions and water behaviour (particularly stratification) as part of a detailed mine-closure plan.

Conclusions

- A groundwater numerical model was constructed to simulate mine related dewatering around Horse Pit after 30 years of mining. The drawdown cone was simulated to the bottom of the final void, some 160 m below surface. The resultant groundwater contours, gradients, and flow patterns were utilised to estimate groundwater ingress into the Horse Pit final void at mine closure. The groundwater drawdown simulation is, allowing for several assumptions, a suitable representation of the envisaged dewatering impacts;
- The conceptualisation and model set-up is a simplified model of actual mining conditions as it assumes constant aquifer hydraulic parameters, hydrochemistry, and no cumulative impacts of Heyford Pit;
- The use of a finite difference model to simulate the groundwater flow within and between layers is suitable for the study even though minor numerical errors may occur due to the dipping angle of the model layers;
- The use of mean annual climate data, based on 100 year data set, allowed for representative input into the scenarios;
- Sensitivity analysis of model parameters ensured that the input into the model were representative, allowing for representative simulations;
- The transient model was used to obtain void equilibrium water levels for various final void configurations and input scenarios. The results all indicate that limited water will be stored in the final void, irrelevant of the configuration, due to limited water input and high evaporation outflow from the model;
- Final void water will deteriorate with time, high and rapid salt accumulation is envisaged for the deep final void. The water in the shallower (regrade) void configurations will become more saline with time but a slower rate; and
- Large void space will be available in all three final void configurations after void equilibrium water level is achieved. This negates any risk of decant from the Horse Pit.

Limitations


URS Australia Pty Ltd (URS) has prepared this report in accordance with the usual care and thoroughness of the consulting profession for the use of BMA and PW Baker and only those third parties who have been authorised in writing by URS to rely on the report. It is based on generally accepted practices and standards at the time it was prepared. No other warranty, expressed or implied, is made as to the professional advice included in this report. It is prepared in accordance with the scope of work and for the purpose outlined in the Proposal dated August 2009.

The methodology adopted and sources of information used by URS are outlined in this report. URS has made no independent verification of this information beyond the agreed scope of works and URS assumes no responsibility for any inaccuracies or omissions. No indications were found during our investigations that information contained in this report as provided to URS was false.

This report was prepared during September 2009 and is based on the information available at the time of preparation. URS disclaims responsibility for any changes that may have occurred after this time.

This report should be read in full. No responsibility is accepted for use of any part of this report in any other context or for any other purpose or by third parties. This report does not purport to give legal advice. Legal advice can only be given by qualified legal practitioners.

Appendix A Final void configurations



This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty Ltd.


	Clean Water Diversion
	Horse Creek Diversion
	Watercourse
	Project Site
	Mining Lease
	Catchments

Kilometers
0 0.25 0.5 1 1.5 2


Scale 1:50 000 (A4)
Datum: AGD84, AMG Zone55


Source:

Client BHP Billiton Mitsubishi Alliance	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title FINAL VOID CONFIGURATION BASE CASE	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1506.mxd	Date: 22-09-2009	Figure: A1




This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty Ltd.


Client  BHP Billiton Mitsubishi Alliance	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title FINAL VOID CONFIGURATION 25% CASE	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1507.mxd	Date: 22-09-2009	Figure: A2




This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty. Ltd.

Client  BHP Billiton Mitsubishi Alliance	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title FINAL VOID CONFIGURATION 10% CASE	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1508.mxd	Date: 22-09-2009	Figure: A3


Appendix B Final void water level figures



Source:

Client  BHP Billiton Mitsubishi Alliance	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title BASE CASE FINAL CONTOURS EXTENT OF WATER IN VOID FROM MAX AND MIN CATCHMENT AREAS	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1509.mxd	Date: 22-09-2009	Figure: B1

This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty. Ltd.



Source:

Client **BMA**
BHP Billiton Mitsubishi Alliance

URS

Project CAVAL RIDGE PROJECT
ENVIRONMENTAL IMPACT STATEMENT
SUPPLEMENT
LONG TERM VOID WATER STORAGE AND QUALITY


Drawn: MG Approved: MST Date: 01-09-2009
Job No: 4262 6420/6158 File No.: 42626158-g-1510.mxd

Title **25% CASE FINAL CONTOURS
EXTENT OF WATER IN VOID FROM
MAX AND MIN CATCHMENT AREAS**

Figure: **B2**

Rev. B
A4

This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty Ltd.



Source:

Client



Project

CAVAL RIDGE PROJECT
ENVIRONMENTAL IMPACT STATEMENT
SUPPLEMENT
LONG TERM VOID WATER STORAGE AND QUALITY

Title

**10% CASE FINAL CONTOURS
EXTENT OF WATER IN VOID FROM
MAX AND MIN CATCHMENT AREAS**



Drawn: MG

Approved: MST

Date: 22-09-2009


Figure: B3

Rev. A


Job No: 4262 6420/6158

File No.: 42626158-g-1511.mxd

A4







Site Cross-Section m (AHD)



This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty.Ltd.



Source:

Client  	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY			Title BASE CASE AND CROSS SECTION	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1512.mxd	Date: 22-09-2009	Figure: B4	



This drawing is subject to COPYRIGHT. It remains the property of URS Australia Pty Ltd.

Client 	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY		Title 25% CASE AND CROSS SECTION	
	Drawn: MG Job No: 4262 6420/6158	Approved: MST File No.: 42626158-g-1513.mxd	Date: 22-09-2009	Figure: B5




This drawing is subject to COP/RIGHT. It remains the property of URS Australia Pty Ltd.

Client BHP Billiton Mitsubishi Alliance 	Project CAVAL RIDGE PROJECT ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENT LONG TERM VOID WATER STORAGE AND QUALITY	Title 10% CASE AND CROSS SECTION
Drawn: MG Job No: 4262 6420/6158	Approved: MST Date: 22-09-2009 File No.: 42626158-g-1514.mxd	Figure: B6
		Rev. A A4


Appendix C Salt balance and Void Volumes figures

Appendix C


C1 Base case average rainfall salt accumulation




C2 Base case average rainfall estimated volumes




C3 25p average rainfall salt accumulation




C4 25p average rainfall estimated volumes




C5 10p average rainfall salt accumulation




C6 10p average rainfall estimated volumes




C7 Base case average rainfall +10% salt accumulation




C8 Base case average rainfall +10% estimated volumes




C9 25p average rainfall +10% salt accumulation




C10 25p average rainfall +10% estimated volumes




C11 10p average rainfall +10% salt accumulation




C12 10p average rainfall +10% estimated volumes




C13 Base case average rainfall -10% salt accumulation




C14 Base case average rainfall -10% estimated volumes




C15 25p average rainfall -10% salt accumulation




C16 25p average rainfall -10% estimated volumes




C17 10p average rainfall -10% salt accumulation




C16 10p average rainfall -10% estimated volumes




C17 Base case average rainfall salt accumulation (combined)




C18 Base case average rainfall estimated volumes (combined)




C19 Base case average rainfall +10% salt accumulation (combined)




C20 Base case average rainfall +10% estimated volumes (combined)



C21 Base case average rainfall -10% salt accumulation (combined)






C22 Base case average rainfall -10% estimated volumes (combined)













Appendix D Drawdown cone predictions

Legend


-  Head Basecase Selection
-  Project Site
-  Mining Lease

**Basecase Initial Head (postmining)
(mAHD)**

-  66 - 70
-  71 - 90
-  91 - 110
-  111 - 130
-  131 - 150
-  151 - 170
-  171 - 190
-  191 - 210
-  211 - 230



Scale 1:40 000 (A4)
Datum: AGD84, AMG Zone55



Source:

Client 
BHP Billiton Mitsubishi Alliance

Project CAVAL RIDGE PROJECT
ENVIRONMENTAL IMPACT STATEMENT
SUPPLEMENT
LONG TERM VOID WATER STORAGE AND QUALITY

Title **DRAWDOWN SIMULATION
(BASE CASE)
AT EQUILIBRIUM (~40YRS)**



Drawn: VE Approved: MST Date: 22-09-2009
Job No: 4262 6420/6158 File No.: 42626158-g-1515.mxd

Figure: **D1**












Rev. A
A4

Legend

-  Head 25% Case
-  Project Site
-  Mining Lease


Head 25% Case

(mAHD)

-  82 - 90
-  91 - 110
-  111 - 110
-  111 - 130
-  131 - 150
-  151 - 170
-  171 - 180
-  181 - 190
-  191 - 200
-  201 - 210
-  211 - 220




Kilometers



Scale 1:40 000 (A4)

Datum: AGD84, AMG Zone55



Source:

Client



Project

CAVAL RIDGE PROJECT
ENVIRONMENTAL IMPACT STATEMENT
SUPPLEMENT
LONG TERM VOID WATER STORAGE AND QUALITY

Title

**DRAWDOWN SIMULATION
(25 PERCENT REGRADE CASE)
AT EQUILIBRIUM (~40YRS)**



Drawn: VE

Approved: MST

Date: 22-09-2009


Figure: **D2**

Rev. A

Job No: 4262 6420/6158

File No.: 42626158-g-1516.mxd

A4



Source:

Client



Project

CAVAL RIDGE PROJECT
 ENVIRONMENTAL IMPACT STATEMENT
 SUPPLEMENT
 LONG TERM VOID WATER STORAGE AND QUALITY

Title

**DRAWDOWN SIMULATION
 (10 PERCENT REGRADE CASE)
 AT EQUILIBRIUM (~40YRS)**



Drawn: VE

Approved: MST

Date: 22-09-2009

Figure: **D3**

Rev. A

Job No: 4262 6420/6158

File No.: 42626158-g-1517.mxd

A4



URS Australia Pty Ltd
Level 16, 240 Queen Street
Brisbane, QLD 4000
GPO Box 302, QLD 4001
Australia

T: 61 7 3243 2111

F: 61 7 3243 2199

www.ap.urscorp.com