

SECTION 7—Use of an EWP, including Boom type, scissor lift (off sealed surfaces), bucket truck etc.			
A "YES" Answer is required for all questions below—or specific controls must be identified.	Yes	No	N/A
Are the persons trained and authorised to operate the EWP?			
Has the pre-start check for the EWP been completed and is the EWP serviceable?			
Is the EWP authorised for use on site? (check equipment compliance sticker)			
Is the slope of the ground less than the cross slope capability of the EWP (check compliance plate)?			
Is the ground area even and firm?			
Will the work platform be operated within its Working Load Limit (WLL)? What is the Working Load Limit (WLL) of the platform:			
Has the impact of inclement weather and the risk of lightning been considered?			
Will the MAC Lightning Tracker system be monitored for the duration of the job?			
Will the wind speed be monitored for the duration of the job? What is the wind speed rating of the machine:			
Will the EWP be set up so it is impossible to approach within 20m of a power line? If "NO" complete on electrical area access permit – MAC-ELC-FRM-003			
Are the persons, including the stand-by person, trained and authorised to operate the EWP?			
What type of EWP is being used: _____ Refer to MAC-STE-PRO-028 MEWP Operation			

i Document Reference - MAC-STE-FRM-182

The EWP must only be driven with the platform extended, if the ground surface is hard, level and free of holes and obstructions.

i Document Reference - MAC-STE-PRO-028